

DISOLA M 3015 & 4015

Description

Disola M 3015 & 4015 are monograde engine oils for High and Medium speed diesel engines.

Applications

Oil specially devised for lubricating High and Medium speed diesel engines at sea and for fishing and river transport applications.

Main and auxiliary naturally-aspirated or supercharged engines of all types and ratings.

Journals, stern tubes and reduction drives / reversing gear.

Recommended for engines running on Gas oil and Marine Diesel oil.

Special Features

- Meets API CF
- High detergent, dispersant and anti-wear capabilities, ensuring cleanliness and long life for engine and transmission systems
- Oil film has good mechanical and thermal strength
- High alkalinity reserve which neutralizes acid combustion products
- Excellent resistance to the action of water

CHARCTERISTIC	UNIT	DISOLA M 3015	DISOLA M 4015
SAE Grade		30	40
Kinematic Viscosity at 40°C	mm ² /s	110	145
Kinematic Viscosity at 100°C	mm ² /s	12	14.2
TBN	Mg KOH/g	14	14

Approvals

Approved by ABC, Deutz, Mireless Blackstone, HiMSEN, Mitsubishi, Niigata, Stork, Wartsila and other major engine builders.

The logo for Lubmarine, featuring the word "Lubmarine" in a stylized font. "Lub" is in red and "marine" is in blue, with a blue wave-like underline beneath the "ine" part.